



29-116 kW

YTPS SERIES

Prismatic - Pipe + Baffle System - 3 Pass

Housing Heating and Central System Heating Boiler

USAGE AREAS

Housing and Mass Housing Heating

FUEL TYPES

Rice Charcoal, Pellet, Hazelnut Charcoal, Pomace

TECHNICAL DATA >>>

YTPS SERIES • 29-290 kW

Prismatic - Pipe + Baffle System - 3 Pass Floor Heating and Central System Boiler



YTPS SERIES • 29-290 kW



POMACE



PELET




HAZELNUT COAL



BRASS COAL

- Multi-functional electronical control panel that is easy to use and elegant, increases safety and decrease consumption of electricity-fuel.
- It provides more heat transfer surface by using stacked baffle layers in place of a pipe
- It has feature of comfortable usage by means of setting the combustion air as per fuel quantity, sleep mode, connection with room thermostat in the electronical control panel.
- Adjustable fan valve helps adjust burn speed according to flue suction.
- Fan and circulation pump automatically shuts down to save energy then the fuel runs out or set temperature cannot be reached.
- High efficiency and cost saving with four-baffle conducted heat transfer surface.
- Sleep mode presents economic and comfortable heating without blowing out for all winter by means of 24-hour-programming feature.
- Large fuel tank (hopper) and fuel sieving system
- More productive combustion is obtained by means of primary and secondary air system with detachable and specially-designed casting ladle.
- Heat loss is minimized by using ceramic-based refractor on boiler's front covers and high-density insulation materials on the body's hot surfaces.
- The boiler can be cleaned easily by virtue of ash discharge system.
- Usage comfort is presented with the specially-designed and optional automatic ignition system.



DIMENSIONS			YTPS									
			25	40	60	80	100	130	160	180	200	250
YTPS	Width(A)	mm	1.300			1.400			1.470		1.600	
YTPS-K	Width(A)	mm	1.550			1.650			1.720		1.850	
YTPS-P	Width(A)	mm	1.300			1.400			1.470		1.600	
YTPS-KP	Width(A)	mm	1.550			1.650			1.720		1.850	
	Length (L)	mm	800	850	860	1.100	1.750	1.350	1.500	1.800	1.450	
	Height (H)	mm	1.450		1.550	1.600	1.600	1.650	1.880	2.000		2.250

TECHNICAL DATA			YTPS								
			25	40	60	80	100	130	160	180	200
Fuel Type Used		Olive Core - Pomace - Pellet - Hazelnut Charcoal - Rice Charcoal									
Heating Power	kW	29	46	70	93	115	151	186	209	232	290
	Kcal	25.000	40.000	60.000	80.000	100.000	130.000	160.000	180.000	200.000	250.000
Combustion Pot Dimensions	mm	340 x 385					435 x 445			550 x 555	
Fuel Capacity (Pomace - Pellet)	kg	95				125		135			
Water Volume	lt	80	94	124	180	216	266	293	340	367	380
Boiler weight	kg	300	341	437	500	620	680	862	970	1.094	1.120
Desired Traction from the Chimney	mbar	0.25 - 0.28	0.31 - 0.33	0.33 - 0.35	0.35 - 0.40			0.42 - 0.45			
Temperature Range	°C	40 - 85									
Maximum Working Pressure	bar	3									
Test Pressure	bar	4.5									
Flue Diameter	Ø mm	165					220		320		
Min. / Max. Flue Temp	°C	170 - 210									
Boiler Input-Output	Ø inç	1	1¼		1½		2		3		
Expansion Tank Input / Output	Ø inç	1				1¼					
Boiler Loading-Unloading	Ø inç	1/2					1				
Electrical Connection	V/Hz	220V - 50Hz									





**Bahçelievler, Bağımsızlık Cd. No:18
35875 • Torbalı, İzmir, Türkiye**

+90 232 462 35 15 • +90 232 486 12 18
+90 533 479 51 27



Technical Support

servis@yagmurteknik.com
+90 534 052 40 34



export@yagmurteknik.com
www.yagmurteknik.com



export@yagmurteknik.com
www.yagmurteknik.com



yağmur teknik

let the expert do the job